



[Visit product page](#)



FOS WATER LOW FOG PRO

L005526

Amazing Low Fog 2200 watt smoke machine that needs only water supply for 200 sqm stages, no need Co2 or Dry ice. DMX 512 , Remote Control LCD screen, 2 dmx channels, heat up time 3.5 mins, fluid consumption 1-60ml/min, fluid-less protection, self cleaning function.

TECHNICAL DETAILS

Effect Descriptions

Professional low fog machine, with flightcase. It produces low lying fog with the ultrasonic atomization method. Includes hose and output nozzle. The main tank fills with approximately 10 liters of water (upper and lower water levels are marked inside the tank). In the fog liquid tank, you add the type (water based only) of the liquid you wish*.

*Professional liquid will provide maximum intensity of the effect, but afterwards the smoke will be scattered around the area. With Co2 simulation liquid you will avoid filling the area with smoke, while you will still have the desired low fog effect. The smoke volume can be always controlled independently via DMX or on board.

Wireless remote, on board and DMX controllable. Fan speed and smoke volume can be adjusted via 2 DMX channels, or from the on board menu. Heat up time: 3,5 minutes.

Dimensions / Installation details

Covers approximately 200 square meters.

Smoke liquid tank capacity: 2,5 lt.

Power supply: 220 / 240 Volt, 50/60 Hz.

Maximum power consumption: 2200 Watt.

Heat up time: 3,5 minutes.

Fluid consumption: 1 to 40 ml per minute.

2 DMX channels: 1: Fan Speed, 2: Fog volume
Dimensions: 760 x 440 x 600 mm (including the wheels)
Weight: 43 Kg.

Packing Details : 47 x 62 x 77 cm - 43 kg

PHOTOS



PRODUCT VIDEO

